

规格	外径	壁厚	重量 (N)		重量N/100 米		长度	
米	毫米	毫米/英寸	米	米	米	米	米	米
02	6.0	45	600	200	1000	200	20 D	10 D
04	6.0	45	600	200	1000	200	20 D	10 D
06	6.0	45	600	200	1000	200	20 D	10 D
08	6.0	45	600	200	1000	200	20 D	10 D
12	6.0	45	600	200	1000	200	20 D	10 D

产品特点

1. 产品特点



- Brand new material**
- > Smooth
 - > Anti-UV
 - > Long-life

- High Quality Fiber**
- > Fast
 - > Long and stability transmission
 - > Low Attenuation.



- High Quality PBT Loose Tube Material**
- > Anti-aging
 - > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.