



www.himakecable.com
info@himakecable.com

GYTS 250um (PSP) YD/T 1155-2001 IEC60794-1

- 1.2 ~ 228
- 2.
- 3.
- 4.
- 5.
- 6.
7. / : -40 °C ~ + 70 °C

0000

00000 00000
000000
0000000000

0000 (000000000000000000000000 info@himakecable.com)

00	000	0000	000000 0000		00 (N)		00000 0N/1000 000	
			00	00	000	00000	00	00
2-24	7/3.0	190	10 D	30%	4950	2500	2000	1000
26-36	7/3.0	200	10 D	30%	4950	2500	2000	1000
38 60	7/3.0	235	10 D	30%	4950	2500	2000	1000
2-24	7/3.6	200	10 D	30%	7100	3500	2000	1000

0000

1.000000000000000000000000, 0000000000000000



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.