



3 种 CCA 电线电缆

电压 300/500V 450/750V

导体 铜芯 CCA

绝缘厚度 0.75 mm

导体 2C 2CE

绝缘 PVC 护套 PVC PE 护套

导体 2C 3C 2CE 护套 E 护套

绝缘 PVC 护套 PVC 护套

导体 铜芯

温度 70°C 90°C

长度 100 m

规格 BVVB H05VVH2-U H07VVH2-R BS6004 624*Y

标准 IEC60277 BS6004 VDE0281 GB/T 5023

重要事項

本製品はRoHS指令に準拠しています。

お問い合わせ

お問い合わせ先: 株式会社ヒメックス

お問い合わせ先: info@himake.co.jp

品名 単位	数量	仕様 単位	仕様 単位	標準寸法	標準寸法 (mm)
2×1.0	1	0.6	0.9	4.8×7.4	46
2×1.5	1	0.7	0.9	5.3×8.3	64
2×1.5	2	0.7	0.9	5.4×8.4	71
2×2.5	2	0.8	1.0	6.2×10.1	97
2×1.01.0(E)	1	0.6	0.9	4.7×8.6	68
2×1.51.0(E)	2	0.7	0.9	5.4×9.6	87
2×2.51.5(E)	2	0.8	1.0	6.2×11.5	120
2×4.01.5(E)	2	0.8	1.0	7.2×13.0	170
2×6.02.5(E)	2	0.8	1.1	8.0×15.0	240

お問い合わせ

ADVANTAGE

WHY US?

Source manufacturers direct, non - agent, no price difference



Professional instrument detection,
strict control, adhere to the quality .



Swing test



Tensile strength test



Print friction test



Temperature test



Insulation resistance test



UV test

PACKAGING LOGISTICS



□□□□□□□□□□□□□□□□□□□□“□□□□”□

