



www.himakecable.com
info@himakecable.com

□□□□□ 600V

□□□ □□□□□□ □□□□□□□□

□□□ 75 °C □□□□□□

□□□□□□□□ □□□□□□□□□□□□ □□□□□

□□□ 100 □□□□□□□□ □□□□□

□□□□□□□□ 75 °C

□□□ ASTM B3□UL83□ASTM B8 UL1581

THW

THW 1000 Kcmil (MCM) 75 °C

THW 14 AWG 1000 Kcmil (MCM) 75 °C

info@himakecable.com

AWG	Strands	Strand Dia (mm)	Strand Dia (in)	Overall Dia (mm)	Overall Dia (in)	Weight (kg/1000ft)
14	1	0.76	4.3	17	33	100
12	1	0.76	4.8	19	47	100
10	1	0.76	5.4	22	68	100
8	1	1.14	6.1	24	100	100
6	1	1.52	7	28	151	100
14	7	0.76	4.5	18	36	100
12	7	0.76	5.1	20	50	100
10	7	0.76	5.8	23	73	100
8	7	1.14	7.4	30	118	100
6	7	1.52	8.5	34	174	100
4	7	1.52	9.8	39	256	100
2	7	2.03	11.3	45	391	100
1	19	2.03	13.5	54	505	1000
1/0	19	2.03	14.6	58	622	1000

THW

1. THW





□□□□□□



3. 10 60





4. 圖 1 為 本 廠 所 製 之 電 纜 盤 之 圖 示 及 裝 載 情 形 。



5. □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□ □□□□□□□□□□□□□□□□



□□ □□□□□□ □□□□□□□□□□□□"□□□□".