



□□□□ 250 / 250V □□□□250/440V □□□□□0.6/1KV □□□□

□□ □□□□5□□□

□□□□□□ 0.50 ~ 4.0sqmm

□□□ 2 C □ 2 C + E □ 3 C + E □ 4 C + E

□□□ V-75 PVC □ V-90 PVC

□□□□ 2 C: □ + □□2 C + E □ □ + □□ + □/□□3 C + E □ □ + □□ + □□ + □/□□4 C + E □ □ + □□ + □□ + □□ + □/□□

□□□ 4V-75 PVC □ 5V-90 PVC

□□□□ □□ □□ □□ □□□□□□

□□□□□□ 75 °C □ 90 °C

□□□ 100□□□□500□□□□□□□□

□□□□ AS / NZS 3191

အထူးသတိပြုရန် အချက်အလက်များကို အောက်ဖော်ပြပါ ဝက်ဘ်ဆိုက်တွင် ရှိပါသည်။

**အချက်အလက်များ**

အောက်ဖော်ပြပါ အချက်အလက်များကို အောက်ဖော်ပြပါ ဝက်ဘ်ဆိုက်တွင် ရှိပါသည်။

**အချက်အလက်များ (အချက်အလက်များကို အောက်ဖော်ပြပါ [info@himakecable.com](mailto:info@himakecable.com) တွင် ရှိပါသည်။)**

အချက်အလက်များ (mm <sup>2</sup> )	အမျိုးအမည်	အချက်အလက်များ	အချက်အလက်များ	အချက်အလက်များ	အချက်အလက်များ (kg/km)
2 x 0.75	OFC 5x5	0.6	0.8	6.30	56
2 x 1.0	OFC 5x5	0.6	0.8	6.70	65
2 x 1.5	OFC 5x5	0.7	0.8	7.70	87
3 x 0.75	OFC 5x5	0.6	0.8	6.7	67
3 x 1.0	OFC 5x5	0.6	0.8	7.0	77
3 x 1.5	OFC 5x5	0.7	0.9	8.3	108
3 x 2.5	OFC 5x5	0.8	1.1	10.1	173

**အချက်အလက်များ**

1. အချက်အလက်များကို အောက်ဖော်ပြပါ ဝက်ဘ်ဆိုက်တွင် ရှိပါသည်။









□□□□□□





3. 10mm 60mm









□□□□□□

□□ □□□□□□ □□ □□□□□□□□□□"□□□□".