



□□□□ 0.6/1KV

□□ 1 □□□2□□□□□□□□

□□□□□□ 1.5 ~ 800sqmm

□□ □□□□

□□□□ 2 C□ □□ + □□□3 C□ □□ + □□ + □□□ 4 C□ □□ + □□ + □□ + □□□5 C□ □□ + □□ + □□ + □□ + □□□□□□□□□□
□□□□ 3 + 1 C□ 4 + 1 C□ 3 + 2 C

□□ PVC□ □□ PVC□□□ PVC□ PE□ □□□□□

□□□□ □□□□□□

□□□□□□ 90 °C

YJLV ZR-YJLV U-1000 R2V RO2V

YJLV ZR-YJLV U-1000 R2V RO2V

IEC60502 BS7889 VDE0276 IEC60332 GB/T12076

Technical Specifications

Compliance with RoHS Directive

Performance

Rated voltage: 0.6 / 1KV

Contact: info@himakecable.com

Conductor Cross-section (mm ²)	Conductor Diameter (mm)	Insulation Thickness (mm)	Overall Cable Diameter (mm)	Weight (kg/1000m)	Approx. Length (m)
1 × 1.5	1.4	0.7	1.4	5.6	52.4
1 × 2.5	1.8	0.7	1.4	6	65.4
1 × 4	2.2	0.7	1.4	6.4	83.1
1 × 6	2.8	0.7	1.4	7	106.7
1 × 10	4.1	0.7	1.4	8.3	157.7
1 × 16	5.1	0.7	1.4	9.3	221.6

Notes

1. All dimensions are in millimeters unless otherwise specified.



□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□