



□□□□ 300/500V 450/750V

□□□ 1 □□2□□□□□□□□ □□□□□□□□

□□□□□□□□ 0.75~ 16sqmm

□□□ 2 C □ 3 C, 2C+E, 3C+E

□□□ PVC □□PVC

□□□□□ 2 C □ □□□ □□□3 C □ □□□ □□□ □□□2C+E: □□□□□□□□□□□□□□

□□□ PVC□□PVC

□□□□□ □□□ □□□□□□□□□□


□□□□□□□□ 70 °C □ 90 °C

□□□ 100 □□□□□□□□□□

□□□□□□□□ BVVB □ H05VVH2-U □ H07VVH2 R □ BS6004 624 * Y

□□□□□□ □□□□□ GB/T 5023 IEC60277

RoHS



info@himakecable.com

Wire Size	Number of Wires	Inner Jacket	Outer Jacket	Dimensions	Weight
2 x 1.0	1	PVC/0.6	PVC/0.9	4.8 x 7.4	46
2 x 1.5	1	PVC/0.7	PVC/0.9	5.3 x 8.3	64
2 x 1.5	2	PVC/0.7	PVC/0.9	5.4 x 8.4	71
2 x 2.5	2	PVC/0.8	PVC/1.0	6.2 x 10.1	97
2x1.0+1.0(E)	1	PVC/0.6	PVC/0.9	4.7 x 8.6	68
2x1.5+1.0(E)	2	PVC/0.7	PVC/0.9	5.4 x 9.6	87
2x2.5+1.5(E)	2	PVC/0.8	PVC/1.0	6.2 x 11.5	120
2x4.0+1.5(E)	2	PVC/0.8	PVC/1.0	7.2 x 13.0	170
2x6.0+2.5(E)	2	PVC/0.8	PVC/1.1	8.0 x 15.0	240



1.





□□□□□□□□



3. 10mm 60mm





