

□□□□□450 / 750V

□□□□□



□□□□ 300 / 500V□450 / 750V

□□ 1□2□□□□□□ □□□□□□

□□□□□□ 0.5□630sqmm

□□ □□PVC

□□□□ □□□□□□□□ □□□□□□□□□□/□□□□□□□□

□□□□□□□ 105°C

□□ □□100□□□□□□□□□□ □□

□□□□□□ PVC□□□PVC□□□PVC□□

□□□□ IEC60227□BS6004□VDE0282

Table 1

Table 1: Dimensions and electrical properties of the cables. The cables are RoHS compliant.

Table 2

Table 2: Dimensions and electrical properties of the cables. The cables are RoHS compliant.

Table 3: Contact information: info@himakecable.com

Dimensions (mm)	Outer Diameter (mm)	Inner Diameter (mm)	Length (mm)	Resistance (MΩ) at 70°C	Weight (g)
1x0.5	0.8	0.8	2.4	0.015	91
1x0.75	0.8	0.8	2.8	0.012	11
1x1.0	0.8	0.8	2.8	0.011	14
1x1.0	0.8	0.8	2.8	0.013	15
1x1.5	0.8	0.8	3.1	0.0123	20.0
1x2.5	0.8	0.8	3.7	0.0103	32
1x4.0	1.0	1.0	4.5	0.0102	47
1x6.0	1.0	1.0	5.1	0.0088	68
1x10	1.0	1.0	6	0.0072	110
1x16	1.0	1.0	6.9	0.0059	170

Table 4

1. Table 4: Dimensions and electrical properties of the cables.



□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□









□□□□□□ □□ □ □□ □□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□



□□□□□□ □□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□



