



□□□□ 0.6/1KV
□□□ 1 □□□□2□□□□□□□□□□□□
□□□□□□□ 1.5 ~ 800sqmm
□□□ □□□□□
□□□□□ 2 C□ □□ + □□□3 C□ □□ + □□ + □□□ 4 C□ □□ + □□ + □□ + □□□5 C□ □□ + □□ + □□ + □□ + □□□□□ 3 + 1 C□
4 + 1 C□ 3 + 2 C□
□□□PE□ □□□□□
□□□□□ □□□□□□□
□□□□□□□90 °C□110□125 °C□ 150 °C
□□□ □□□□□□□
□□□□□□□ WDZ-YJY□U-1000 R2V RO2V

IEC60502 BS7889 VDE0276 IEC60332 GB/T12076

Technical Specifications

Compliance with RoHS Directive

Performance Characteristics

Rated voltage: 0.6 / 1KV

Contact us at info@himakecable.com

Cable Size	Outer Diameter (mm)	Conductor Diameter (mm)	Insulation Thickness (mm)	Weight (kg/km)	Approx. Length (m)
1 x 1.5	1.4	0.7	1.4	5.6	52.4
1 x 2.5	1.8	0.7	1.4	6	65.4
1 x 4	2.2	0.7	1.4	6.4	83.1
1 x 6	2.8	0.7	1.4	7	106.7
1 x 10	4.1	0.7	1.4	8.3	157.7
1 x 16	5.1	0.7	1.4	9.3	221.6

Notes

1. All dimensions are in millimeters unless otherwise specified.



2. □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□