

□□□□:



□□□□: 0.6/1KV

□□: 1□□□□2□□□□□, □□□□

□□□□□□: 1.5 ~ 800 sqmm

□□: □□□□□i

□□□□: 2C: □ + □, 3C: □ + □ + □, 4C: □ + □ + □ + □, 5C: □ + □ + □ + □ + □, □□□□□□□□, □□ 3 + 1 c, 4 + 1 c, 3 + 2 c

□□: □□□□□□□□□□□□□□ PVC

□□□□: □□□□□□

□□□□□□: 90°C

□□: □□□□□□

Model: YJV, ZR-YJV, U-1000 R2V,RO2V

Standards: IEC60502, BS7889, VDE0276, IEC60332,GB/T12076

**Material:**

RoHS compliant, Halogen free.

**Properties:**

Rated voltage U<sub>0</sub>/U 0.6/1KV, Frequency 50/60Hz, Temperature (Operating, Storage)

Contact: [info@himakecable.com](mailto:info@himakecable.com)

Cross-section (mm <sup>2</sup> )	Weight (kg/km)	Conductor diameter (mm)	Insulation thickness (mm)	Outer diameter (mm)	Approx. length (m)
1 x 1.5	1.4	0.7	1.4	5.6	52x4
1 x 2.5	1.8	0.7	1.4	6	65x4
1 x 4	2.2	0.7	1.4	6.4	83x1
1 x 6	2.8	0.7	1.4	7	106x7
1 x 10	4.1	0.7	1.4	8.3	157x7
1 x 16	5.1	0.7	1.4	9.3	221x6

**Notes:**

1. Please refer to the technical specifications for detailed information.



2. 0000000 0000000 00000000000000000000, 00000000000000

0000





□□□□□□





3. 10 60 international ly







4. We 提供 各種 規格 之 電纜 產品， 品質 優良， 價格 公道。







5. 〇〇〇〇〇〇 〇〇〇〇〇〇, 〇〇〇〇〇〇〇〇, 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇

