



□□□□ 0.6/1KV

□□ 1 □□□□2□□□□□□□□□□

□□□□□□ 1.5 ~ 800sqmm

□□ □□□□

□□□□ 2 C□ □□ + □□□3 C□ □□ + □□ + □□□ 4 C□ □□ + □□ + □□ + □□□5 C□ □□ + □□ + □□ + □□ + □□□□□□□□□□
□□□□ 3 + 1 C□ 4 + 1 C□ 3 + 2 C

□□ PVC□ □□ PVC□□□ PVC□ PE□ □□□□□

□□□□□ □□□□□□□

□□□□□□□ 90 °C

□□ □□□□□□

YJV ZR-YJV YJY WDJ-YJY U-1000 R2V RO2V

IEC60502 BS7889 VDE0276 IEC60332 GB/T12076

Properties

Compliant with RoHS

Applications

0.6 / 1KV

Contact: info@himakecable.com

Conductor Cross-section (mm ²)	Outer Diameter (mm)	Stranding (mm)	Insulation Thickness (mm)	Overall Diameter (mm)	Weight (kg/100m)
1 x 1.5	1.4	0.7	1.4	5.6	52.4
1 x 2.5	1.8	0.7	1.4	6	65.4
1 x 4	2.2	0.7	1.4	6.4	83.1
1 x 6	2.8	0.7	1.4	7	106.7
1 x 10	4.1	0.7	1.4	8.3	157.7
1 x 16	5.1	0.7	1.4	9.3	221.6

Notes

1. Properties are based on standard conditions.





□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□