



□□□□**H05V-U**□**H07V-U**

□□□□ 300 / 500V□450 / 750V

□□ 1□2□□□□□□□ □□

□□□□□□□□ 0.5□10sqmm

□□ PVC□□□PVC

□□□□ □□□□□□□□□□ □□□□□□□□□□□□□□□□

□□□□□□□□ 70°C□90°C□105°C

□□ □□100□□□□□ □□

□□□□□□□ BV□BLV□BLVR□H05V-U□H07V-U□BS6004 6491X

RoHS

RoHS

RoHS

RoHS

info@himakecable.com

导体截面积 mm ²	导体结构	绝缘材料 厚度	导体直径 mm	绝缘电阻 70°C MΩ·km	重量 kg/km
1×0.5	1根导体	PVC / 0.6	2.4	0.015	8.1
1×0.75	1根导体	PVC / 0.6	2.6	0.012	10.9
1×1.0	1根导体	PVC / 0.6	2.8	0.011	13.7
1×1.5	1根导体	PVC / 0.7	3.3	0.011	20.0
1×2.5	1根导体	PVC / 0.8	3.9	0.010	31.1
1×4.0	1根导体	PVC / 0.8	4.4	0.0085	45.7
1×6.0	1根导体	PVC / 0.8	4.9	0.0070	65.2
1×10	1根导体	PVC / 1.0	6.4	0.0070	112

RoHS

1. ...



□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□







□□□□□□ □□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□



