

□□□□:



□□□□: 450/750V

□□: 1□□2□□□□□□ □□□□□□□□

□□□□□□□□: 1.0 ~ 300 sqmm

□□: □□□□□□□□□□□□□□□□□□

□□□□: □□, □□, □□, □□, □□, □□, □□, □□, □□/□□□□□□□□□□

□□: PVC□PE□□□□□□□□

□□□□: □□□□□□□□□□□□□□

□□□□□□: 70°C, 90°C, 105°C

□□: □□100□, □□ □□

規格: BVV, BVVR, H05VV-U, H07VV-U, H05VV-R, H07VV-R, BS6004 6491X

規格: IEC60277, BS6004, VDE0281, IEC/T 5023, IEC60332

特徴:

RoHS 対応

仕様:

ケーブル径、絶縁厚、外皮厚、重量

お問い合わせ: (Eメール: info@himakecable.com)

規格 (mm ²)	規格 (mm)	規格 (mm)	規格 (mm)	70°C (MΩ•km)	規格 (mm/ft)
1×1.0	PVC/0.6	PVC/0.8	4.3	0.011	26
1×1.5	PVC/0.7	PVC/0.8	4.8	0.011	33
1×2.5	PVC/0.8	PVC/0.8	5.4	0.01	44
1×6.0	PVC/0.8	PVC/0.9	6.6	0.007	84
1×10	PVC/1.0	PVC/0.9	8.2	0.007	138
1×16	PVC/1.0	PVC/0.9	9.0	0.0050	204
1×25	PVC/1.2	PVC/1.0	11.7	0.0050	315
1×35	PVC/1.2	PVC/1.1	12.9	0.0040	415
1×50	PVC/1.4	PVC/1.3	15.2	0.0045	589
1×70	PVC/1.4	PVC/1.4	16.9	0.0035	790

お問い合わせ:

- お問い合わせ先: info@himakecable.com



2. 0000000 0000000 00000000000000000000, 00000000000000

0000



□□□□□□



3. 10 60 international ly





4. We 提供 鋼絲 鋼絲繩 鋼絲網, 鋼絲 鋼絲, 鋼絲繩鋼絲網鋼絲繩鋼絲網



5. 000000 000000, 00000000, 00000000000 000000000000000000000000.



