



www.himakecable.com
info@himakecable.com

产品特性

1. 符合IEC60332-1-2标准
2. 符合IEC60332-3标准
3. 符合IEC60331-33标准
4. 符合IEC60331-34标准
5. 护套材料 PVC OFNP PU

应用

适用于各种工业环境; 适用于各种工业环境

联系我们 (info@himakecable.com)

| Model | Core Diameter (mm) | Cladding Diameter (mm) | Core Diameter (N) | | Cladding Diameter | | Strength (N/mm ²) |
|-------|--------------------|------------------------|-------------------|----|-------------------|------|-------------------------------|
| 2 | 3.0 | 7.6 | 80 | 40 | 20 D | 10 D | 500 |
| 2 | 5.0 | 19 | 160 | 80 | 20 D | 10 D | 500 |

Introduction

1. Introduction of the product



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.