

产品概述

额定电压 300/500V/450/750V 系列

额定电流 1 ~ 250A 额定电压

导体截面积 0.5 ~ 400sqmm

绝缘材料 PVC/PPVC

额定温度 70 °C/90 °C/105 °C

额定长度 100 米/卷

符合标准 BV、BLV、H05V-U、H07V-U、H05V R、H07V R、BS6004 6491X

符合标准 IEC60277、BS6004、GB/T 5023、BS7211、IEC60332、VDE0281 GB/T19666

产品特点

符合 RoHS 标准

技术参数

本产品符合 GB/T 19666-2005 标准

性能指标

导体截面积 (mm ²)	导体材料	绝缘材料	导体直径 (mm)	70 °C 绝缘电阻 (MΩ•km)	额定电压 (V)
1 × 0.5	1 股铜线	PVC/0.6	2.4	0.015	8.1
1 × 0.75	1 股铜线	PVC/0.6	2.6	0.012	10.9
1 × 1.0	1 股铜线	PVC/0.6	2.8	0.011	13.7
1 × 1.5	1 股铜线	PVC/0.7	3.3	0.011	20.0
1 × 2.5	1 股铜线	PVC/0.8	3.9	0.010	31.1
1 × 4.0	1 股铜线	PVC/0.8	4.4	0.0085	45.7
1 × 6.0	1 股铜线	PVC/0.8	4.9	0.0070	65.2

产品应用

1. 本产品适用于室内布线





□□□□□□□□



3. 10mm 60mm







