



□□□□ 300/300V

□□□ 5□□□□□□□□

□□□□□□□ 0.50 ~1.0sqmm

□□□ PVC, □□ PVC□□PVC, LSZH

□□□□ Red + Black, Red + White, Red with white stripe, white with black stripe or embossing stripe, white with embossing stripe or other color requested

□□□□□□□ 70 °C□90 °C, □□LSZH□□□150 °C

□□□ 100 □□□□□□□□ □□

□□□□□□□ Figure 8 cable, Speaker cable

□□□□□ IEC60277□AS/NZS 5000.2

RoHS

RoHS

RoHS

RoHS

RoHS (info@himakecable.com)

RoHS	RoHS	RoHS	RoHS 0 °C	RoHS	RoHS 70 °C
mm ²)	RoHS	RoHS	Ω/m	RoHS	(mΩ·km)
2 × 0.3	PVC/0.6	2.1 × 03.9	69.2	71.2	0.016
2 × 0.4	PVC/0.6	2.2 × 04.3	48.6	49.6	0.014
2 × 0.5	PVC/0.6	2.7 × 05.3	39	40.1	0.016
2 × 0.75	PVC/0.8	2.9 × 05.7	26	26.7	0.014
2 × 1.0	PVC/0.8	3.1 × 06.1	20	20	0.012

RoHS

1. RoHS



2. □□□

□□□□□□



□□□□□□□□



3. 10mm 60mm





