



□□□□ **Ho7V-U IEC60227**□□

□□□□ 300 / 500V□450 / 750V

□□□ □□□□□□□□□□□□□□□□

□□□□□□□□ 0.75□300sqmm

□□□ PVC□□□PVC□□□□□□

□□□□□ □□□

□□□□□□□□ 70°C□90°C□□□□□□□□□□150°C

□□ □□100□□□□□□ □□

□□□□□□□ BV□BLV□BLVR□H05V-U□BS6004 6491X□H07V0R□H05Z-U□H07Z-R

□□□□□ IEC60277□BS6004□ VDE0281□GB / T 5023

## RoHS

RoHS

## RoHS

RoHS

[info@himakecable.com](mailto:info@himakecable.com)

mm <sup>2</sup>		PVC /	mm	70°C MΩ•m	mm/ft
1×0.5	1	0.6	2.4	0.015	8.1
1×0.75	1	0.6	2.6	0.012	10.9
1×1.0	1	0.6	2.8	0.011	13.7
1×1.5	1	0.7	3.3	0.011	20.0
1×2.5	1	0.8	3.9	0.010	31.1
1×4.0	1	0.8	4.4	0.0085	45.7
1×6.0	1	0.8	4.9	0.0070	65.2
1×10	1	1.0	6.4	0.0070	112

## RoHS

1. RoHS





□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□









XXXXXXXXXX XXXX XXXXXXXXX XXX





□□□□□□ □□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□



