

H01N2-D

□□□□□□□□

DIN VDE 0282-803

□□□□: 100 □

□□□□:

-□□□-20°C □ + 90°C

-□□□0°C □ + 50°C



□□: □□:□□□□□□□□5□, □□: □□□□□□□□

□□: □□□□□□□□□□□□□□□□□□ (□□□□ □□)□

□□ □□ □□	□□ □	□□ □□	□□ □	□□
□□ ²	□□	□□	□□/□□	□□/□□
10	20	100	950	1670
16	20	115	1512	2365
25	20	130	2344	3436
35	20	145	3370	4632
50	22	170	4854	6490
70	24	190	6767	8843
95	26	215	9183	1.1800
120	28	240	1.1107	1.3890
150	30	260	1.3773	1.7070
185	32	290	1.6883	2.0750

□□□□:

1. □□□ □□□□□□, □□□□□□□□□□□□□□□□□□□



2. 0000000 0000000 000000000000000000, 00000000000000

0000



□□□□□□



3. 10 60







4.We 〇〇〇〇 〇〇〇 〇 〇〇〇〇 〇〇〇〇〇〇, 〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇



5. 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇, 〇〇〇〇〇〇〇〇〇〇〇〇〇〇



