



450/750V

2-core

0.75~4.0sqmm

2C, 4C, 2C+E

+ X-HF-110

2 C: ; 4 C ; 2 C + E ;

HFS-110-TP

110 °C

HF-110

AS / NZS 5000.2 AS / NZS 3013-WS52W

ROHS COMPLIANT

ROHS COMPLIANT.

TECHNICAL SPECIFICATIONS

Technical specifications and performance characteristics of the cable are detailed in the accompanying datasheet.

CONTACT INFORMATION (info@himakecable.com)

Cable Size (mm ²)	Core Count	Conductor Size (mm)	Insulation Thickness (mm)	Overall Diameter (mm)	Weight (kg/100m)
2 x 0.75	2	0.7	TC	1.2	9.5
2 x 1.5	2	0.7	TC	1.2	9.9
4 x 1.5	4	0.7	TC	1.2	11.7
2 x 0.75 + E	2	0.7	TC	1.2	9.8
2 x 1.5 + E	2	0.7	TC	1.2	10.2
4 x 1.5 + E	4	0.7	TC	1.8	13.0

ORDERING INFORMATION

1. Minimum order quantity is 100 meters.



2.□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□

Quality Comparison

Purity of copper



Excellent 99.93% Oxygen Free Copper ,
Bright color with long life time .



Inferior Copper including a lot of impurity
Easy heat, short life Easily cause fire

Flame Test



Excellent No spread , and release a little
white smoke



Inferior Keep burning , and pop a lot of black
HCL toxic smoke

Resistance Test



Excellent low resistivity, high conductivity



Inferior High resistivity, High consumption .
Easy to burning .

Eccentricity Ratio



Excellent Insulation thickness uniformity



Inferior Insulation thickness nonuniform
Easy electric leakage fire disaster,

High Pressure Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

High Temperature Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

Low Temperature Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

3. 10mm 60mm





5. □□□□□□ □□□□□□□□□□□□□□□□□□□□ □□□□ □□□□□□□□□□□□□□



□□□□□□

□□ □□□□□□ □□ □□□□□□□□□□"□□□□".