



□□ □□ 50/66KV □ 64/66KV □ 64/110KV □ 127/220KV □ 290/550KV

□□□□□□□□□□ ≤ 800mm<sup>2</sup> □□□□□□□□□□ > 800mm<sup>2</sup> □□

□□□□□□□□□□ ≥ 500mm<sup>2</sup> □□□□□□□□□□

□□ □□□□□□□□

□□□□ □□□□□□

□□□□□ □□□□□□□

□□□□ □□□□; □□ □□□□□□□□□□□□

□□ □□□□□□

□□□□□□ □□□□□ □□□□□□□□□□□□□□□□□

□□□□□□ 240 ~ 3000sqmm

□□□□□□ 90 °C □ 105 °C

□□ □□□□□□

□□□□□□ YJQ02 YJQ03 □ YJLQ02 YJLQ03

Properties

Operating temperature 90°C, Storage temperature 105 °C

Operating temperature 250 °C

25 D, D

Properties

66KV

Contact (info@himakecable.com)

mm <sup>2</sup> )	mm	mm	mm	mm	mm	mm
400	23.8	27	2.4	5	116	14342
500	26.6	27	2.4	5	119	15629
630	30	26	2.4	5	121	16946
800	33.8	25	2.4	5	123	19069
1000	38.7	24	2.6	5	126	20970
1200	42.4	24	2.6	5	129	23270
1400	45.8	24	2.6	5	133	25525
1600	49	24	2.6	5	136	27774
1800	51.9	24	2.6	5	139	30112
2000	54.7	24	2.8	5	142	32383
2500	61.2	24	2.8	5	149	37780

Properties

1. Properties







□□□□□□



3. 10mm 60mm









□□□□□□□□ □□□□□□□□“□□□□”□□□