



□□ □□□ 50/66KV□ 64/66KV□ 64/110KV□ 127/220KV□290/550KV

$\square \leq 800\text{mm}^2$ $\square > 800\text{mm}^2$

$\geq 500\text{mm}^2$

□ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □ □

--	--	--	--	--	--	--	--	--	--	--	--	--	--

□□□□□ □□□□□; □□ □□□□□□□□□□□□□□□□

1000000000

--	--	--	--	--	--	--	--

240 ~ 3000sqmm

90 °C~105 °C

UL 1059

IEC 60840:1999

Technical Data

90°C, 105 °C

5 250 °C

25 D, D

Technical Data

66KV

UL 1059

Contact Us (info@himakecable.com)

mm ²)	mm	mm	mm	mm	mm	mm
400	23.8	27	2.4	5	116	14342
500	26.6	27	2.4	5	119	15629
630	30	26	2.4	5	121	16946
800	33.8	25	2.4	5	123	19069
1000	38.7	24	2.6	5	126	20970
1200	42.4	24	2.6	5	129	23270
1400	45.8	24	2.6	5	133	25525
1600	49	24	2.6	5	136	27774
1800	51.9	24	2.6	5	139	30112
2000	54.7	24	2.8	5	142	32383
2500	61.2	24	2.8	5	149	37780

Technical Data

1. UL 1059





2. □□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□
□□□□



□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□