

产品概述

额定电压300/500 V

额定电压 300/300V/300/500V

符合 IEC60228/VDE0295 5 类 K 类

导体截面积 0.5~16mm²

护套材料 PVC/LSZH/PUR

护套颜色 黑色/灰色/蓝色

护套材料 PVC/LSZH/PUR/EVA

护套厚度: 0.5~1.5mm

工作温度 -50~90°C 存储温度 -40~90°C

导体直径 100 微米

导体材料 YY/KVVR/LiYY/RVV

符合 IEC60277/BS6500/VDE0250/GB/T 9330

产品特点

阻燃、耐高温、耐低温、耐腐蚀、抗老化

应用范围

广泛应用于工业、农业、交通、能源、建筑等行业

联系我们

导体截面积 mm ²	导体根数	导体直径-Ø	护套厚度 mm	护套重量 g/m	护套长度 m/卷
2×0.75	5	0.21	5.6	14.4	39
3×0.75	5	0.21	5.9	21.6	47
4×0.75	5	0.21	6.4	28.8	57
5×0.75	5	0.21	7	36	68
7×0.75	5	0.21	7.6	50.4	87
10×0.75	5	0.21	9.6	72	119
12×0.75	5	0.21	10.3	86.4	145
18×0.75	5	0.21	12	129.6	206





□□□□□□



3. 15 60 internationally







