



AS / NZS3013

额定电压 450 / 750V

导体 聚氯乙烯绝缘

导体标称截面 0.75-4.0 mm²

导体 2C-4C-2C + E.

导体 聚氯乙烯+ X-HF-110

导体 2C-1C+1C; 4C-1C+1C+1C; 2C + E-1C+1C

导体 HFS-110-TP

导体 聚氯乙烯

导体 110°C

导体 100-500mm

导体 HF-110-TP

导体 AS / NZS 5000.2-AS / NZS 3013 - WS52W

导体

导体 符合RoHS

导体

导体 符合RoHS

导体 info@himakecable.com

导体截面mm ²	导体	导体截面mm	导体	导体截面mm	导体
2×0.75	OFC	0.7	TC	1.2	9.5
2×1.5	OFC	0.7	TC	1.2	9.9
4×1.5	OFC	0.7	TC	1.2	11.7
2×0.75 + E	OFC	0.7	TC	1.2	9.8
2×1.5 + E	OFC	0.7	TC	1.2	10.2
4×1.5 + E	OFC	0.7	TC	1.8	13.0

导体





□□□□□

Quality Comparison

Purity of copper



Excellent

99.93% Oxygen Free Copper ,
Bright color with long life time .



Inferior

Copper including a lot of impurity
Easy heat, short life Easily cause fire

Flame Test



Excellent

No spread , and release a little
white smoke



Inferior

Keep burning , and pop a lot of black
HCL toxic smoke

Resistance Test



Excellent


low resistivity, high conductivity



Inferior

High resistivity,High consumption .
Easy to burning .

Eccentricity Ratio



Excellent

Insulation thickness uniformity



Inferior

Insulation thickness nonuniform
Easy electric leakage fire disaster,

High Pressure Test



Excellent

Jacket no any damage



Inferior

Jacket damaged , reveal conductor

High Temperature Test



Excellent

Jacket no any damage



Inferior

Jacket damaged , reveal conductor

Low Temperature Test



Excellent

Jacket no any damage



Inferior

Jacket damaged , reveal conductor







