



□□□□ 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□□ 2 □□□□□□□□□□

□□□□□□□ 25 ~ 1000sqmm

□□□ □□□□□

□□□□□ 1 C□ □□□□□ 3 C□ □ + □ + □□ □□□□

□□□□□ □□□□□□□ + □□□□□□□ + □□□□□□□

□□□□□□□□□□

□□□ PVC□ □□ PVC□ □□PVC

□□□□□ □□□□□□□

□□□□□□□□ 90 °C

□□□ □□□□□□□

□□□□□□□□ YJV22, ZR-YJV22

Technical Specifications

Compliance with IEC60502 BS6622 GB/T12706 VDE0276 IEC60332 and RoHS

Product Details

Product Code: 26/35, Material: PVC, Insulation Thickness: 4.5mm

Contact: info@himakecable.com

Conductor Size (mm <sup>2</sup> )	Insulation Thickness (mm)	Overall Diameter (mm)	Weight (kg/100m) (A)	Weight (kg/100m) (B)	Weight (kg/100m) (C)
3 x 25	4.5	50.6	126	154	3358
3 x 35	4.5	53	151	184	3816
3 x 50	4.5	56.2	181	218	4494
3 x 70	4.5	60	225	267	5333
3 x 95	4.5	64.1	273	318	6359
3 x 120	4.5	67.5	311	360	7338
3 x 150	4.5	71.1	353	404	8493
3 x 185	4.5	75	402	456	9824
3 x 240	4.5	80.3	473	531	11894
3 x 300	4.5	86.9	540	598	14826

Notes

1. All dimensions are in millimeters unless otherwise specified.



2. □□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□

□□□□



□□□□□□



3. 10mm 60mm









5. 〇〇〇



□□□□□□□□ □□□□□□□□“□□□□”□□□