



□□□□ 3.6/6KV

□□ 2 □□□□□□□□

□□□□□□ 25 ~ 1000sqmm

□□ □□□□

□□□□□□ □□□

□□□□ □□□□□□ + □□□□□□ + □□□□□□

□□ PVC □□ PVC □□PVC

□□□□ □□□□□□

额定电压 90 °C

额定电压

额定电压 YJV

符合 IEC60502、BS6622、GB/T12706、VDE0276 IEC60332

产品特点

符合 RoHS 标准

规格

符合 GB 3.6/6 标准

联系我们 (mailto:info@himakecable.com)

导体截面积 (mm ²)	绝缘厚度 (mm)	导体直径 (mm)	护套厚度 (A) (mm)	护套直径 (A) (mm)	重量 (kg/100m)
25	2.5	17.4	165	160	505
35	2.5	18.4	205	190	616
50	2.5	19.9	245	225	788
70	2.5	21	305	275	999
95	2.5	23.5	370	330	1276
120	2.5	24.9	430	375	1532
150	2.5	26.7	490	425	1849
185	2.5	28.3	560	480	2197
240	2.5	30.7	665	555	2763
300	2.5	33.7	765	630	3391
400	2.5	38.9	890	725	4433
500	2.5	42.2	1030	825	5474
630	2.5	54.6	1190	940	6751

联系我们

1. 联系我们





□□□□□□



3. 10mm 60mm



□□□□□□□□ □□□□□□□□“□□□□”□□□