





www.himakecable.com
info@himakecable.com

电压等级 18/30KV 21/35KV 26/35KV

芯数 2 芯

导体截面积 25 ~ 1000sqmm

护套材料

铠装材料

结构形式 导体 + 绝缘 + 铠装 + 护套

护套材料 PVC 铠装材料 PVC 护套材料 PVC

其他材料

额定温度 90 °C

额定电压

额定电压 YJV, YJV62,YJV72

符合 IEC60502、BS6622、GB/T12706、VDE0276 IEC60332

产品特点

符合 RoHS 指令

产品特点

导体截面 26/35mm² 导体材料 铜

产品特点

符合 RoHS 指令

产品特点

导体截面 3.6/6mm² 导体材料 铜

联系我们 (info@himakecable.com)

导体截面 (mm ²)	导体材料	导体材料	导体材料(A)	导体材料 (A)	导体材料 mm ² /mm
50	9.3	35.8	245	225	1551
70	9.3	37.5	305	275	1792
95	9.3	39.5	370	330	2127
120	9.3	40.7	425	375	2415
150	9.3	42.5	485	420	2778
185	9.3	44.1	555	475	3164
240	9.3	46.5	650	555	3764
300	9.3	48.9	745	630	3782
400	9.3	52.3	870	720	4444
500	9.3	57.7	1000	825	5518
630	9.3	61.6	1160	940	5926

产品特点

1. 符合 RoHS 指令



2. 111111111111111111 111111111111111111111111111111111111

1111



□□□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□