



□□□□ 3.6/6KV,6/6KV,6/10KV,8.7/10KV,8.7/15KV,12/20KV,18/30KV,21/35KV,26/35KV

□□□ 2 □□□□□□□□□□

□□□□□□□ 25 ~ 1000sqmm

□□□ □□□□□

□□□□□ 1 C□ □□□□3 C□ □ + □ + □□ □□□□

□□□□□ □□□□□□□ + □□□□□□□ + □□□□□□□

□□□□□□□□□□

□□□□ PE, LSZH, LSOH

□□□□□ □□□□□□□□

□□□□□□□□ 90 °C

□□□ □□□□□□□□

□□□□□□□□ YJY33, WDZ-YJY33

Technical Specifications

Compliance with IEC60502 BS6622 GB/T12706 VDE0276 IEC60332 and RoHS

Product Details

Product Code: 26/35, Material: PVC, Insulation: XLPE

Contact: info@himakecable.com

Conductor Size (mm ²)	Conductor Diameter (mm)	Overall Diameter (mm)	Weight (kg/100m)	Length (m)	Volume (m ³)
3 x 25	4.5	53.8	128	155	4821
3 x 35	4.5	56.2	155	185	5366
3 x 50	4.5	59.4	185	219	6156
3 x 70	4.5	63.2	230	268	7096
3 x 95	4.5	67.3	276	320	8265
3 x 120	4.5	70.7	316	362	9312
3 x 150	4.5	75.6	358	407	11445
3 x 185	4.5	79.5	409	460	12910
3 x 240	4.5	84.8	482	535	15220
3 x 300	4.5	90.2	546	601	17581
3 x 400	4.5	100.2	647	695	21722

Notes

1. All dimensions are in millimeters unless otherwise specified.





□□□□□□



3. 10mm 60mm





□□□□□□□□ □□□□□□□□“□□□□”□□□