



0000 3 0000000000000000 **TPS** 000000

00000 300/500V 450/750V

000 0000000000000000 CCA

00000000 0.75 16000

000 2C 2CE

000 PVC 000 PVC PE 000000000000

00000 3C 000000 2CE 000000 E 000000

00 PVC 000 PVC 000000000000

00000: 0000000000000000

000000000000 70°C 90°C

000 00 100 00000000

00000000 BVVB 0H05VVH2-U 0H07VVH2-R BS6004 624*Y 0000000000000000 TPS 00

000000 IEC60277 BS6004 VDE0281 GB/T 5023

重要事項

本製品はRoHS指令に準拠しています。

お問い合わせ

お問い合わせ先: 株式会社ヒマケ

お問い合わせ先: info@himake.co.jp

品名 単位	数量	仕様 内容	仕様 内容	寸法 (mm)	重量 (g)
3×1.0	1	0.6mm	0.9mm	4.8×8.7	64
3×1.5	1	0.7mm	0.9mm	5.3×11.1	91.6
3×1.5	2	0.7mm	0.9mm	5.4×11.4	97
3×2.5	2	0.8mm	1.0mm	6.2×13.8	132
2×1.01.0(E)	1	0.6mm	0.9mm	4.7×8.6	62
2×1.51.0(E)	2	0.7mm	0.9mm	5.4×9.6	87
2×2.51.5(E)	2	0.8mm	1.0mm	6.2×11.5	120
2×4.01.5(E)	2	0.8mm	1.0mm	7.2×13.0	170
2×6.02.5(E)	2	0.8mm	1.1mm	8.0×15.0	240

お問い合わせ

ADVANTAGE

WHY US?

Source manufacturers direct, non - agent, no price difference



Professional instrument detection,
strict control, adhere to the quality .



Swing test



Tensile strength test



Print friction test



Temperature test



Insulation resistance test



UV test

PACKAGING LOGISTICS



☐ " ☐ ☐ ☐ ☐ "

