



□□□□ 300/500V 450/750V

□□□ 1 □□2□ 2 □□□□□□ □□□□□□

□□□□□□ 1.0 ~ 35sqmm

□□□ 2 C ~ 7 C

□□□ XLPE, LSZH, LSOH

□□□□□ □□□ □□□ □□□ □□□ □□□ □□□□□□□□□□

□□□ LSZH, LSOH

□□□□□ □□□ □□□□□□□□

□□□□□□□ 90 °C□110□125 °C□ 150 °C

□□□ 100 □□□□□□□□□□□□

□□□□□□□BYJY), WDZ-BYJY), H05ZZ-U,H07ZZ-U, H05ZZ-R, H07ZZ-R

IEC60277 BS7211 IEC60332 IEC61034 IEC60754 HD22.9 VDE0282 GB/T19666

Product Description

RoHS Compliant

Technical Specifications

Technical specifications and performance characteristics.

Contact Information (info@himakecable.com)

Cross-section of conductor (mm <sup>2</sup> )	Kind of Conductor	Insulation Thickness (mm)	Sheath Thickness (mm)	Average Max. Outer-diameter (mm)	Product Approx. weight (kg/km)	Min. insulation resistance (MΩ.km)
2×2.5	1	PVC/0.8	PVC/1.2	11.5	116.99	0.01
2×2.5	2	PVC/0.8	PVC/1.2	12	124.84	0.009
2×4	1	PVC/0.8	PVC/1.2	12.5	154.02	0.0085
2×4	2	PVC/0.8	PVC/1.2	13	162.49	0.0077
3×1.5	1	PVC/0.7	PVC/1.2	10.5	105.86	0.011
3×1.5	2	PVC/0.7	PVC/1.2	11	110.82	0.01
3×2.5	1	PVC/0.8	PVC/1.2	12	149.34	0.01
3×2.5	2	PVC/0.8	PVC/1.2	12.5	159.02	0.009

Notes

1. Additional technical details and notes.



2.□□□

□□□□□□



□□□□□□□□



3. 10mm 60mm













