海迈电缆
Himake Cable
紧套光纤
Tight buffer fiber
芳纶
Aramid yarn
子单元护套
Subunit Jacket
LSZH护套
LSZH Jacket
非金属加强芯
FRP strength member
CE
SAA
UL
CB
RoHS
www.himakecable.com
info@himakecable.com

## 产品特性

1.多芯光缆制成
2.多芯光缆有独立芳纶纱护套加强
3.2 ~ 144 芯
4.非金属中心加强元件

## 产品应用

通过到室内的水平和垂直铺设，天花板敷设，表面铺设，等。适合跳线和扎着马尾辫。

## 产品参数（更多详细信息，请给我们发电子邮件： info@himakecable.com)

| 光纤芯数 | 光缆外径 | 重量 | 允许抗拉强度 (N) | | 允许侧压力 （N/100 毫米） | | 允许 弯曲半径 （毫米） | |
|---|---|---|---|---|---|---|---|---|
| 计数 | （毫米） | （公斤/公里） | 短 期限 | 长 期限 | 短 期限 | 长 期限 | 短 期限 | 长 期限 |
| 12 | 15.5 | 205 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 24 | 15.5 | 205 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 36 | 17.5 | 255 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 48 | 17.5 | 255 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 60 | 19.5 | 320 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 72 | 19.5 | 320 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 96 | 22 | 395 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |
| 144 | 28 | 597 | 1500 | 500 | 1500 | 600 | 20 D | 10 D |

## 产品优势

1.导体是由高品质的光纤制成，它具有低色散和衰减，保证很好的信号和数据传输能力.

**Brand new material**

> **Smooth**

> **Anti-UV**

> **Long-life**

**High Quality Fiber**

> **Fast**

> **Long and stability transmission**

> **Low Attenuation.**

**High Quality PBT Loose Tube Material**

> **Anti-aging**

> **Good Protection**

# ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.

## Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing

# APPLICATION

✔ Pipeline

✔ Overhead

✔ Direct bury

Packaging & Shipping

# PACKING AND SHIPPING

- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.

info@himakecable.com