



□□□□□ 0.6/1 K V

□□□ □□□□□□ □□□□□ IEC60228 5□

□□□□□□□ 1.5 ~ 25 □□<sup>2</sup>

□□□ □□□□□□□□□□

□□□□□□□ □□□□□□□ □□□□□□□

□□□ □□□□

□□□□□ □□□□□ □□□ □□□ □□□□□

□□□ 100 □□□□□□ □□□□□

□□□□□□□ 125 °C

□□□ 3 TÜV PFG 1169/08.2007 □ RoHs 2002/95/ec □□□

TÜV UL

UL 157 (UL 157)

UL 157 (UL 157) is a standard for fire-resistant cables.

UL 168 (UL 168)

UL 168 (UL 168) is a standard for fire-resistant cables.

Contact Us (info@himakecable.com)

Cable Size (mm <sup>2</sup> )	UL Rating	Weight (m w/m)	Outer Diameter (mm)	Inner Diameter (mm)	Length (m)	Weight (kg)
2.5	UL 157	8.21	0.50	0.50	4.60	46.0
4.0	UL 157	5.09	0.50	0.50	5.00	60.0
6.0	UL 157	3.39	0.50	0.50	5.60	80

For more information, please contact us.

UL 168 (UL 168)

1. UL 168 (UL 168) is a standard for fire-resistant cables.











□□□□□□







3. 10 60













5. 社區活動



□□ □□□□□□ □□ □□□□□□□□□□"□□□□".