



□□□□ □□□□□ □□□□□□1350-H19□□

□□□□□□ PE □XLPE

□□□□□□3□

□□□□□ □□□□AAC□AAAC□ ACSR

□□□□□□□1□

□□□□□ Quadruplex□□□□□□—□□□□□□

□□□ □□□□□□□□

□□□□ ASTM B 230□ B-231□ B-232 □ B-399□ ICEA S-76-474

規格

600mm² 75 °C 90 °C

仕様

6/1 ASTM B 399 6201

75 °C 40 °C

500

お問い合わせ (info@himakecable.com)

Code name	Phase conductor structure (AWG-No.)	XLPE insulation thickness (mm)	Bare conductor structure (AWG-No.)	Bare conductor Rated strength (kg)	Approx. cable weight (kg/km)	Ampacity (A)
Morochuca	6-solid	1.14	6-6/1	540	229	78
Chola	6-7	1.14	6-6/1	540	237	78
Morgan	4-solid	1.14	4-6/1	844	344	103
Hackney	4-7	1.14	4-6/1	844	356	103
Palomino	2-7	1.14	2-6/1	1293	557	136
Albino	1-19	1.52	1-6/1	1610	699	158
Standardbred	1/0-7	1.52	1/0-6/1	1987	859	182
Costena	1/0-19	1.52	1/0-6/1	1987	862	182
Chicoteagues	2/0-7	1.52	2/0-6/1	2404	1060	210
Grullo	2/0-19	1.52	2/0-6/1	2404	1063	210

お問い合わせ

1. お問い合わせ



□□□□□□



3. 10 60 internationally





Figure 4. The process of cable spool production and transportation



5. 2014年 5月 10日 2014年 5月 10日 2014年 5月 10日 2014年 5月 10日



2014年 5月 10日

2014年 5月 10日 2014年 5月 10日“2014年”。

