



□□□□ 300/500V 450/750V

□□□ 1 □□2□□□□□□□□ □□□□□□□□

□□□□□□□□ 0.75~ 16sqmm

□□□ 2 C□ 3 C

□□□ PVC□ □□PVC

□□□□□ 2 C□ □□□ □□□3 C□ □□□ □□□ □□□□□□□□

□□□ PVC□□□PVC

□□□□□ □□□ □□□ □□□□□□□□


□□□□□□□□ 70 °C□90 °C

□□□ 100 □□□□□□□□□□

□□□□□□□□ BVVB□H05VVH2-U□H07VVH2 R□BS6004 624 * Y

□□□□□□ □□□□□ GB/T 5023 IEC60277□BS6004□VDE0281

RoHS



info@himakecable.com

Core Size (mm ²)	Number of Cores	Inner Jacket	Outer Jacket	Overall Dimensions (mm)	Weight (kg/100m)
2 x 1.0	1	PVC/0.6	PVC/0.9	4.8 x 7.4	46
2 x 1.5	1	PVC/0.7	PVC/0.9	5.3 x 8.3	64
2 x 1.5	2	PVC/0.7	PVC/0.9	5.4 x 8.4	71
2 x 2.5	1	PVC/0.8	PVC/1.0	5.9 x 9.7	93
2 x 2.5	2	PVC/0.8	PVC/1.0	6.2 x 10.1	97
2 x 4.0	1	PVC/0.8	PVC/1.0	6.9 x 11.2	140
3 x 1.5	1	PVC/0.7	PVC/0.9	5.3 x 11.6	91
3 x 1.5	2	PVC/0.7	PVC/0.9	5.4 x 11.9	97
3 x 2.5	1	PVC/0.8	PVC/1.0	5.9 x 13.7	133



1.





□□□□□□□□



3. 10mm 60mm





