



□□□□ 300/300V

□□□ 5□□□□□□□□□

□□□□□□□ 0.3 ~1.0sqmm□□□□□□□□□□16sqmm

□□□ PVC, □□ PVC□□□PVC

□□□□ Red + Black, Red + White, Red with white stripe, white with black stripe or embossing stripe, white with embossing stripe or other color requested

□□□□□□□ 70 °C□90 °C

□□□ 100 □□□□□□□□ □□

□□□□□□□RVB, H03VH-F, H05VH-F, Figure 8 cable

IEC60277 BS6500 VDE0281 GB/T 5023 IEC60332

RoHS

RoHS

RoHS

RoHS

info@himakecable.com

导体截面积 (mm <sup>2</sup> )	绝缘材料	导体直径 (mm)	20 °C 直流电阻 (Ω/km)		20 °C 直流电阻 (mΩ·km)
2 × 0.3	PVC/0.6	2.1 × 03.9	69.2	71.2	0.016
2 × 0.4	PVC/0.6	2.2 × 04.3	48.6	49.6	0.014
2 × 0.5	PVC/0.6	2.7 × 05.3	39	40.1	0.016
2 × 0.75	PVC/0.8	2.9 × 05.7	26	26.7	0.014
2 × 1.0	PVC/0.8	3.1 × 06.1	20	20	0.012

RoHS

1. RoHS







□□□□□□□□



3. 10mm 60mm











