



[www.himakecable.com](http://www.himakecable.com)  
[info@himakecable.com](mailto:info@himakecable.com)

□□□□□ 300/300V

□□□ 5□□□□□□□□□

□□□□□□□ 0.3 ~2.5sqmm

□□□ PVC, □□ PVC□□□PVC

□□□□□ □□ + □□ + □□□□ □□ + □□□□□ + □□□□□□□□□□

□□□□□□□□ 70 °C□90 °C

□□□□ 100 □□□□□□□□□□ □□

□□□□□□□□RV□□H03V-S□□H05V-S

IEC60332-1

RoHS

IEC60332-2

info@himakecable.com

IEC60332-1 IEC60332-2	IEC60332-1 IEC60332-2	IEC60332-1 IEC60332-2	IEC60332-1 20 °C Ω/km	IEC60332-2 70 °C (mΩ•km)	IEC60332-1 (A)
2 x 0.3	4.3	13.4	69.2	0.016	7.4
2 x 0.4	4.6	17	48.2	0.014	9.0
2 x 0.5	6.0	24	39.0	0.014	10
2 x 0.75	6.2	31	26.0	0.014	13
2 x 1.0	6.6	34	19.5	0.011	16
2 x 1.5	7.2	45	13.3	0.010	20
2 x 2.5	8.2	65	7.98	0.009	27

IEC60332-3

1.







□□□□□□□□



3. 10mm 60mm











