

工作温度: 70°C~90°C

长度: 100m

绝缘材料: KVV32, ZR-KVV32

符合标准: IEC60277, BS6500, VDE0250, GB / T9330, IEC60332

产品特性

本产品符合 RoHS 环保要求

技术参数

本产品适用于各种工业、商业及民用场合

450/750v 规格

联系我们: info@himakecable.com

规格	护套厚度	绝缘厚度	导体直径	导体间距	导体直径	导体间距	护套厚度	绝缘厚度
(mm2)	450/750V 0.6/1 K V		450/750V 0.6/1 K V		450/750V 0.6/1 K V		450/750V 0.6/1 K V	
2 × 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	16.9	18.3	656	725
2 × 6	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.9	19.3	744	816
2 × 10	PVC/1.0	PVC/1.0	PVC/1.7	PVC/1.8	21.7	21.9	1019	1028
3 × 2.5	PVC/0.8	PVC/0.8	PVC/1.5	PVC/1.8	16.5	17.1	634	657
3 × 4	PVC/0.8	PVC/1.0	PVC/1.5	PVC/1.8	17.5	19	727	803

联系我们

1. 联系我们: info@himakecable.com





□□□□□□



3. 10 60







4. 此項業務目前正積極爭取中，預計於下月開始運作。



