

□□□□:



□□□□: 450/750V

□□: 1□□□□2□□□□□5□ □□□□□□□□□

□□□□□□□□□: 0.75 ~ 10 sqmm

□□: PVC□□□PVC□Rohs □□PVC

□□□□: □□5□□□□□□□□□□5□□□□□□□□□□□□□□□□□□□

□□: PVC□□□PVC□□□PVC

□□□□: □□, □□□□□□

□□□□□□:70°C□90°C

□□: 100□□□□□□□□□□

□□□□□□: KVV□KVVR□YY

□□□□: IEC60277, BS6500, VDE0250, GB/T9330, IEC60332

□□□□:

□□□□ □□□□□□□□□□□ □□□□□□□□□□Rohs□□□□□

□□□□:

□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□

□□□□ (450/750 v):

(□□□□□□□□□□□□: info@himakecable.com info@himakecable.com)

□□□□ (mm ²)	□□□□ □□	□□□□ □□	□□ □□□ □□	□□□□ (□□/□□)	□□□□□□□□20°C (ω/km)	□□□□□□70°C (mΩ•km)
2x0.75	pvc/0□6	pvc/1□2	7□5	67.72	24□5	0.012
2x1□0	pvc/0□6	pvc/1□2	7.82	76□2	18□1	0.011
2x1□5	pvc/0□7	pvc/1□2	8.74	97.71	12□1	0.011
2x2□5	pvc/0□8	pvc/1□2	9.96	133□4	7.41	0.01
2x4	pvc/0□8	pvc/1□2	10□9	173.65	4.61	0.0085

□□□□:

1. □□□ □□□□□□□□□□□□□□□□□□□□



2. 0000000 0000000 000000000000000000, 00000000000000

0000



□□□□□□



3. 10mm 60mm







4. We 〇〇〇〇 〇〇〇 〇 〇〇〇〇 〇〇〇〇〇〇, 〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇



5. 〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇, 〇〇〇〇〇〇〇〇〇〇〇〇〇〇



