

□□□□450/750V

□□ □□□□2□□□□□

0.75~4.0sqmm

2C, 4C, 2C+E

+ X-HF-110

2 C: + ; 4 C + + + + 2 C + E + + +

+ + +

HFS-110-TP

+

110 °C

+

HF-110 +

AS / NZS 5000.2 AS / NZS 3013-WS52W

ROHS

ROHS.

CONTACT

Information regarding this product can be found on our website.

CONTACT (info@himakecable.com)

| Conductor (mm ²) | Core | Core Dia | Insulation | Core Dia | Overall Dia |
|------------------------------|------|----------|------------|----------|-------------|
| 2 x 0.75 | 2C | 0.7 | TC | 1.2 | 9.5 |
| 2 x 1.5 | 2C | 0.7 | TC | 1.2 | 9.9 |
| 4 x 1.5 | 2C | 0.7 | TC | 1.2 | 11.7 |
| 2 x 0.75 + E | 2C | 0.7 | TC | 1.2 | 9.8 |
| 2 x 1.5 + E | 2C | 0.7 | TC | 1.2 | 10.2 |
| 4 x 1.5 + E | 2C | 0.7 | TC | 1.8 | 13.0 |

CONTACT

1. Information regarding this product can be found on our website.





□□□□

Quality Comparison

Purity of copper



Excellent 99.93% Oxygen Free Copper ,
Bright color with long life time .



Inferior Copper including a lot of impurity
Easy heat, short life Easily cause fire

Flame Test



Excellent No spread , and release a little
white smoke



Inferior Keep burning , and pop a lot of black
HCL toxic smoke

Resistance Test



Excellent low resistivity, high conductivity



Inferior High resistivity, High consumption .
Easy to burning .

Eccentricity Ratio



Excellent Insulation thickness uniformity



Inferior Insulation thickness nonuniform
Easy electric leakage fire disaster,

High Pressure Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

High Temperature Test



Excellent Jacket no any damage




Inferior Jacket damaged , reveal conductor

Low Temperature Test



Excellent Jacket no any damage



Inferior Jacket damaged , reveal conductor

3. 10mm 60mm





4. 〇〇〇〇〇 〇〇〇 〇 〇〇〇〇 〇〇〇〇〇〇〇〇〇 〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇〇



5. □□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□



□□□□□□

□□ □□□□□□ □□ □□□□□□□□□□"□□□□".