



聚氯乙烯绝缘

PVC Insulated

聚氯乙烯被覆

PVC Jacket

铝箔麦拉

Aluminum mylar



镀锡铜线编织

Tinned copper braid shielded

铜芯导体

Copper conductor



www.himakecable.com
info@himakecable.com

□□□□ 300/300V 300/500V

□□ 5□□□□□□□□

□□□□□□ 0.5 ~ 6.0sqmm

□□ PVC, □□ PVC□□PVC

□□□□ □□□□□□□□ □□ □□□□/ □□□□□□□□

□□□□: □□□□□□□□□□□□□□□□+□□□□

□□□□: 40~85%

□□ PVC, □□ PVC□□PVC

RVVP 100 70 °C 90 °C

RVVP, H05VVC4V5-F

IEC60277 BS6500 VDE0281 GB/T 5023 IEC60332

RVVP 100 70 °C 90 °C

RVVP, H05VVC4V5-F

IEC60277 BS6500 VDE0281 GB/T 5023 IEC60332

RVVP 100

RVVP 100 70 °C 90 °C

RVVP 100

RVVP 100 70 °C 90 °C

RVVP 100 (info@himakecable.com)

| RVVP 100 | RVVP 100 | RVVP 100 | RVVP 100 20 °C Ω/km | RVVP 100 70 °C (mΩ·km) |
|----------|----------|----------|---------------------|------------------------|
| 2 × 2.5 | 9.0 | 136.5 | 7.98 | 0.008 |
| 2 × 4.0 | 11.8 | 209.5 | 4.95 | 0.007 |
| 2 × 6.0 | 13.4 | 2.632 | 3.30 | 0.006 |
| 3 × 0.5 | 6.6 | 58.3 | 39.0 | 0.012 |
| 3 × 0.75 | 7.3 | 76.9 | 26.0 | 0.010 |
| 3 × 1.0 | 8.1 | 87.6 | 19.5 | 0.010 |
| 3 × 1.5 | 9.1 | 117.6 | 13.3 | 0.009 |
| 3 × 2.5 | 9.8 | 169.1 | 7.98 | 0.008 |

RVVP 100

1. RVVP 100 70 °C 90 °C





□□□□□□□□



3. 10mm 60mm





