



緊套光纖 Tight buffer fiber
芳綸 Aramid yarn
PVC護套 PVC Jacket



www.himakecable.com
info@himakecable.com

產品

1. 緊套光纖
2. 芳綸
3. PVC護套
4. PVC OFNP PU

規格

MTRJ

(info@himakecable.com)

項目	規格	単位	試験回数 (N)		試験回数N/100		試験結果	
			合格	不合格	合格	不合格	合格	不合格
1.6	0.6	2.80	150	80	500	100	30%	10 D
1.8	0.6	3.00	150	80	500	100	30%	10 D
2.0	0.9	4.25	150	80	500	100	30%	10 D
2.4	0.9	5.00	150	80	500	100	30%	10 D
2.8	0.9	6.60	150	80	500	100	30%	10 D
3.0	0.9	7.00	150	80	500	100	30%	10 D

試験結果

項目	規格	単位	試験回数 (N)		試験回数N/100		試験結果	
			合格	不合格	合格	不合格	合格	不合格
2.0	0.60	15	1000	300	1000	500	30%	10 D
2.4	0.60	16	1000	300	1000	500	30%	10 D
2.8	0.60	18	1000	300	1000	500	30%	10 D
3.0	0.60	18	1000	300	1000	500	30%	10 D

試験結果

1.試験結果を評価し、試験結果を報告する。



Brand new material

- > Smooth
- > Anti-UV
- > Long-life

High Quality Fiber

- > Fast
- > Long and stability transmission
- > Low Attenuation.



High Quality PBT Loose Tube Material

- > Anti-aging
- > Good Protection

ADVANCED PRODUCTION EQUIPMENT

Advanced Production Equipments can guarantee qualified product.



Optic Fiber Cable Testing

- Fiber Testing
- Testing after fiber coloring
- Testing after fiber stranding
- Testing after fiber optic cable jacketing



APPLICATION



✓ Pipeline



✓ Overhead



✓ Direct bury

Packaging & Shipping

PACKING AND SHIPPING



- Each single length of cable shall be reeled on wooden Drum suitable for long-distance shipment.