



额定电压 300/500V 450/750V

导体 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

导体截面积 0.5 ~ 10sqmm

绝缘材料 PVC

导体材料 铜

工作温度 70 °C 90 °C 105 °C

长度 100 米

符合标准 BV, H05V-U, BS6004 6491 X

符合标准 IEC60277 BS6004 GB/T 5023 VDE0281

□ □ □ □ □

□□□□ □□□ □□□□□□□□□□□□□□ □□□□□□□□ Rohs □□□

□ □ □ □

[illegible]

0000 (0000000000000000 info@himakecable.com)

□□□□ □□□ ²)	□□□□	□□□□ □□□□	□□□□□□□□ □□□□	□ 70 °C □□□□□□ (MΩ•km)	□□ □□□ □□□/□□□
1 × 0.5	1 □□□□□	PVC/0.6	2.4	0.015	8.1
1 × 0.75	1 □□□□□	PVC/0.6	2.6	0.012	10.9
1 × 1.0	1 □□□□□	PVC/0.6	2.8	0.011	13.7
1 × 1.5	1 □□□□□	PVC/0.7	3.3	0.011	20.0
1 × 2.5	1 □□□□□	PVC/0.8	3.9	0.010	31.1
1 × 4.0	1 □□□□□	PVC/0.8	4.4	0.0085	45.7
1 × 6.0	1 □□□□□	PVC/0.8	4.9	0.0070	65.2
1 × 10	1 □□□□□	PVC/1.0	6.4	0.0070	112

□□□□

1.





□□□□□□□□



3. 10mm 60mm





5.



Page 10

" "

