

____ 300/500V_450/750V ___

 $0.75 \sim 400$ sqmm

DDD PVCD DDPVC

□□□□□□ 70 °C□90 °C□105 °C

____BVR_H05V-R_H07V-R_BS6004 6491 X

____ GB/T 5023_ IEC60277_BS6004_VDE0281

0000 00000 0000000000 00000000 Rohs 000

$\square\square\square\square\square$ ($\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square$ info@himakecable.com)

				70 °C □□□□□	
$\square\square\square^2$)				(MΩ∙km)	
1 × 0.75	2 0000	PVC/0.6	2.8	0.014	11.8
1 × 1.0	2 0000	PVC/0.6	3.0	0.013	14.3
1 × 1.5	2 0000	PVC/0.7	3.4	0.010	21.3
1 × 2.5	2 0000	PVC/0.8	4.2	0.009	34.4
1 × 4.0	2 0000	PVC/0.8	4.8	0.0077	47.0
1 × 6.0	2 0000	PVC/0.8	5.4	0.0065	68.7
1 × 10	2 0000	PVC/1.0	6.8	0.0065	116
1 × 16	2 00000	PVC/1.0	8.0	0.0050	168
1 × 25	2 0000	PVC/1.2	9.8	0.0050	275
1 × 35	2 0000	PVC/1.2	11	0.0040	372
1 × 50	2 0000	PVC/1.4	13	0.0045	503
1 × 70	2 0000	PVC/1.4	15.0	0.0035	708
1 × 95	2 0000	PVC/1.6	17.2	0.0035	979
1 × 120	2 0000	PVC/1.6	19.0	0.0032	1207
1 × 150	2 0000	PVC/1.8	21.0	0.0032	1493
1 × 185	2 0000	PVC/2.0	23.5	0.0032	1861
1 × 240	2 0000	PVC/2.2	26.5	0.0032	2437
1 × 300	2 0000	PVC/2.4	29.5	0.0030	3066
1 × 400	2 0000	PVC/2.6	33.5	0.0028	3895





2.000000000000000000000000000000000000
--





























