



断面 積(mm <sup>2</sup> )	芯数	外皮 仕様	外径 (mm)	70 °C 直流抵抗 (MΩ・km)	重量 (kg/1000m)
1 × 0.75	2 芯	PVC/0.6	2.8	0.014	11.8
1 × 1.0	2 芯	PVC/0.6	3.0	0.013	14.3
1 × 1.5	2 芯	PVC/0.7	3.4	0.010	21.3
1 × 2.5	2 芯	PVC/0.8	4.2	0.009	34.4
1 × 4.0	2 芯	PVC/0.8	4.8	0.0077	47.0
1 × 6.0	2 芯	PVC/0.8	5.4	0.0065	68.7
1 × 10	2 芯	PVC/1.0	6.8	0.0065	116
1 × 16	2 芯	PVC/1.0	8.0	0.0050	168
1 × 25	2 芯	PVC/1.2	9.8	0.0050	275
1 × 35	2 芯	PVC/1.2	11	0.0040	372
1 × 50	2 芯	PVC/1.4	13	0.0045	503
1 × 70	2 芯	PVC/1.4	15.0	0.0035	708
1 × 95	2 芯	PVC/1.6	17.2	0.0035	979
1 × 120	2 芯	PVC/1.6	19.0	0.0032	1207
1 × 150	2 芯	PVC/1.8	21.0	0.0032	1493
1 × 185	2 芯	PVC/2.0	23.5	0.0032	1861
1 × 240	2 芯	PVC/2.2	26.5	0.0032	2437
1 × 300	2 芯	PVC/2.4	29.5	0.0030	3066
1 × 400	2 芯	PVC/2.6	33.5	0.0028	3895

ヒマケケーブル

1. ヒマケケーブル株式会社







□□□□□□□□



3. 10mm 60mm













