



□□□□ 0.6/1 K V

□□ □□□□□ □□□□ IEC60228 5□

□□□□□□ 1.5 ~ 25 □□²

□□ □□□□□□□□

□□□□□□ □□□□□□ □□□□□□

□□ □□□□

□□□□ □□□□ □□ □□ □□□□

□□ 100 □□□□□□ □□□□

□□□□□□ 125 °C

□□ 3 TÜV PFG 1169/08.2007 □ RoHs 2002/95/ec □□□

TÜV UL

UL 157 (UL 157)

UL 157 (UL 157) is a standard for fire-resistant cables.

UL 1685 (UL 1685)

UL 1685 (UL 1685) is a standard for fire-resistant cables.

Contact Us (info@himakecable.com)

Cable Size (mm ²)	UL Rating	Weight (m w/m)	Outer Diameter (mm)	Inner Diameter (mm)	Length (m)	Weight (kg)
2.5	UL 157	8.21	0.50	0.50	4.60	46.0
4.0	UL 157	5.09	0.50	0.50	5.00	60.0
6.0	UL 157	3.39	0.50	0.50	5.60	80

UL 157 (UL 157) is a standard for fire-resistant cables.

UL 1685 (UL 1685)

1. UL 1685 (UL 1685) is a standard for fire-resistant cables.



2. 下列各数中，与 10 最接近的数是（ ）

A. 9



□□□□□□



3. 10 60





4. [unreadable text]



5. □□□□□□□□ □□□□□□□□□□□□□□□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□



□□ □□□□□□ □□ □□□□□□□□□□"□□□□".