



www.himakecable.com
info@himakecable.com

□□□□□ 0.6/1KV

□□□ 2□□□□□□□□□□□□

□□□□□□□□ 16 ~ 630sqmm

□□□ V-90 PVC

□□□□□□□□□□

□□□ 5V-90 PVC

□□□□□□ □□□□□□□□□□

□□□□□□□□ 90 °C

□□□ 100 □□□ □□□□□□□□□□ □□

XLPE SDI

AS/NZS 5000.1

Table 1: Technical Specifications

This product complies with the requirements of the RoHS Directive

Table 2: Cable Dimensions

XLPE SDI cables are available in various sizes and configurations. For more information, please contact our sales team at glanding@himakecable.com.

Contact Information

Cable Size	Outer Diameter (mm)	Inner Diameter (mm)	Outer Diameter (mm)	Outer Diameter (mm)	Weight (kg/100m)
1 x 16	16.0	0.8	1.4	9.3	210
1 x 25	25.0	0.9	1.4	10.5	300
1 x 35	35.0	0.9	1.4	11.5	400
1 x 50	50.0	1.0	1.4	12.9	520
1 x 70	70.0	1.1	1.4	14.7	730
1 x 95	95.0	1.1	1.5	17.2	1010
1 x 120	120.0	1.2	1.5	19.6	1230
1 x 150	150.0	1.4	1.6	21.3	1520

Table 3: Additional Information

1. All dimensions are in millimeters unless otherwise specified.





□□□□□□



3. 10mm 60mm







□□□□□□

□□ □□□□□□ □□ □□□□□□□□□□"□□□□".