

\_\_\_\_ 300/500V\_450/750V \_\_\_

DDD PVCDDDPVC

\_\_\_\_\_ 70 °C 90 °C 105 °C

\_\_\_\_ GB/T 5023\_IEC60332 IEC60277\_BS6004\_VDE0281

## 

## $\square\square\square\square\square$ ( $\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square\square$ info@himakecable.com)

				□ 70 °C □□□□□□	
				(MΩ•km)	
$1 \times 1.0$	PVC/0.6	PVC/0.8	4.3	0.011	26
$1 \times 1.5$	PVC/0.7	PVC/0.8	4.8	0.011	33
1 × 2.5	PVC/0.8	PVC/0.8	5.4	0.01	44
$1 \times 6.0$	PVC/0.8	PVC/0.9	6.6	0.007	84
1 × 10	PVC/1.0	PVC/0.9	8.2	0.007	138
1 × 16	PVC/1.0	PVC/0.9	9.0	0.0050	204
1 × 25	PVC/1.2	PVC/1.0	11.7	0.0050	315
1 × 35	PVC/1.2	PVC/1.1	12.9	0.0040	415
1 × 50	PVC/1.4	PVC/1.3	15.2	0.0045	589
1 × 70	PVC/1.4	PVC/1.4	16.9	0.0035	790





















# 



3. 000**10**00000 00000 **60** 00000000000









