



Nominal Voltage: 450/750V

Conductor: Class 2 plain annealed copper stranded

Conductor nominal cross section area: 0.75~400sqmm

Insulation: PVC, PE, LSZH

Insulation color: Red, Blue, Brown, Grey, Black, Blue, Yellow, White, Green/Yellow or other color requested

Max. operating temperature: 70°C, 90°C, 105°C

Package: 100 meters per roll for small size cable and wooden package for big size cable, or as per requirement

Main product model: BVR, H05V-R, H07V-R, BS6004 6491X, H07Z-R

Product standard: IEC60277, BS6004, VDE0281, GB/T 5023

Product characteristics:

High temperature resistance, low temperature resistance, flame retardant and high electrical conductivity, also fire resistance, UV resistance or Rohs compliant can be available as per request.

Product application:

The cables are used for general power supply and distribution purpose, as building wire for power,

lighting, etc in house, and power supply to electrical appliance, suitable for use in conduit and for fixed, protected installation.

1. 如何 選擇 合適 的 函數 模型





2. 0000000 0000000 00000000000000000000, 00000000000000

0000





□□□□□□□□







3. 10mm 60mm









4.We 提供 鋼筋 及 鋼絲網 產品, 鋼筋 鋼絲, 鋼絲網產品等







5. 環境教育活動、環境保護活動、環境教育活動の成果





