

海迈电缆  
Himake Cable



www.himakecable.com  
info@himakecable.com

□□□□ 0.6/1K V

□□ 1 □□□ 2 □□□□□□□□

□□□□□□ 1.5 ~ 1000sqmm

□□ XLPE, PE, LSZH, LSOH

□□□□ 2 C□ □□ + □□□3 C□ □□ + □□ + □□□4 C□ □□ + □□ + □□ + □□□5 C□ □□ + □□ + □□ + □□ + □□

□□□ □□□□□□□□□□□□□□□□

□□□ PE, LSZH, LSOH

□□□□□ □□□□□□□

□□□□□□□ 70 °C□90 °C

名称 阻燃型

规格型号 YJY22-WDZ-YJY22

执行标准 IEC60502-BS7870 GB/T12706-VDE0276, IEC60332

### 特性

本产品符合 阻燃型 阻燃型RoHS

### 应用

本产品适用于 0.6/1KV 及以下电压等级

联系我们 (mailto:info@himakecable.com)

规格 (mm <sup>2</sup> )	外径 (mm)	重量 (kg/km)	导体截面积(A)	绝缘截面积(A)	重量 (kg/km)
1 × 25	14.7	0.9	162	202	467
1 × 35	15.7	0.9	197	244	574
1 × 50	17.2	1	237	292	746
1 × 70	10.7	1.1	299	365	973
1 × 95	19.1	1.1	361	437	1235
1 × 120	20.7	1.2	417	500	1501

### 备注

1. 本产品符合 阻燃型







□□□□□□



3. 10 60







4. 請於報告書中說明各項產品之出貨及運送過程，並附上相關之照片。





