

NYA



NYA

300 / 500V 450 / 750V

2

0.75 400sqmm

PVC PVC

/

70°C 90°C 105°C

100

BVR H05V-R H07V-R BS6004 6491X

IEC60277 BS6004 VDE0281 GB / T 5023

Rohs

info@himakecable.com

規格 mm ²	規格	規格 mm	規格 mm	規格70°C MΩ•mm	規格 mm/mm
1×0.75	2mm	PVC / 0.6	2.8	0.014	11.8
1×1.0	2mm	PVC / 0.6	3.0	0.013	14.3
1×1.5	2mm	PVC / 0.7	3.4	0.010	21.3
1×2.5	2mm	PVC / 0.8	4.2	0.009	34.4
1×4.0	2mm	PVC / 0.8	4.8	0.0077	47.0
1×6.0	2mm	PVC / 0.8	5.4	0.0065	68.7
1×10	2mm	PVC / 1.0	6.8	0.0065	116
1×16	2mm	PVC / 1.0	8	0.0050	168
1×25	2mm	PVC / 1.2	9.8	0.0050	275
1×35	2mm	PVC / 1.2	11	0.0040	372
1×50	2mm	PVC / 1.4	13	0.0045	503
1×70	2mm	PVC / 1.4	15.0	0.0035	708
1×95	2mm	PVC / 1.6	17.2	0.0035	979
1×120	2mm	PVC / 1.6	19.0	0.0032	1207
1×150	2mm	PVC / 1.8	21.0	0.0032	1493
1×185	2mm	PVC / 2.0	23.5	0.0032	1861
1×240	2mm	PVC / 2.2	26.5	0.0032	2437
1×300	2mm	PVC / 2.4	29.5	0.0030	3066
1×400	2mm	PVC / 2.6	33.5	0.0028	3895

規格

規格 規格





□□□□□□□□







[illegible]



