





www.himakecable.com
info@himakecable.com

额定电压 300V

额定温度 90℃

额定电压

额定电压 300V 额定电压 300V 额定电压 300V

额定电压 2000 额定电压 610 额定电压 610

额定电压 80 °C

额定电压 UL1007 UL758 UL1581 CSA22.2

UL規格ケーブル

UL規格ケーブルはUL VW-1 と CSA FT1 を満たしています

UL規格ケーブル

UL 1007 PVC 絶縁ケーブル

お問い合わせ (info@himakecable.com):

UL規格 & CSA 規格	径 (mm)	外径 (mm)	断面積 (mm²)	長さ (m)	重量 (kg) 20 °C 時 Ω/KM
UL1007 単線	30	7/0.100	0.41	1.10	381.00
	28	7/0.127	0.41	1.20	239.00
	26	7/0.160	0.41	1.30	150.00
	24	11/0.160	0.41	1.40	94.20
	22	17/0.160	0.41	1.60	59.40
	20	21/0.178	0.41	1.80	36.70
UL1007 2線	26	7/0.160	0.41	1.30	140.00
	24	7/0.200	0.41	1.40	88.70
	22	7/0.250	0.41	1.60	54.70
UL1007 3線	26	1/0.404	0.41	1.25	143.00
	24	1/0.511	0.41	1.35	89.30
	22	1/0.634	0.41	1.50	56.40
	20	1/0.813	0.41	1.65	35.20

お問い合わせ

1. お問い合わせ先



2. 在下列各题中，选择正确的答案。

1. 1. 1. 1.



□□□□□□



3. 10 60



海迈电缆
Himake Cable





www.himakecable.com
info@himakecable.com



00 00000000 000000000000"0000".